

MATERIAL SAFETY DATA SHEET

1. IDENTIFICATION OF THE PRODUCT

SVEZA Exterior Birch Plywood

Synonyms

Exterior Russian birch plywood
FSF birch plywood
Exterior Baltic birch plywood

SUPPLIER

SVEZA-Les, OOO

CONTACT INFORMATION:

Greenwood Office Center, 17, Putikovo, Krasnogorsk District, 72nd km of MKAD, Moscow Region, Russia, 143441.

Tel: +7(495) 783 00 35

Fax: +7(495) 783 00 34

2. HAZARDS IDENTIFICATION

EYE CONTACT

Product in the supplied form can emit small amounts of formaldehyde which can unlikely cause temporary irritation or a burning sensation.

Further processing of the product – can produce wood dust which can cause mechanical irritation.

SKIN CONTACT

Birch may evoke allergic contact dermatitis in sensitized individuals.

Handling panels may cause splinters which lead to skin irritation.

INHALATION

In a well ventilated work areas the concentration of formaldehyde will not exceed World Health Organization standard of 0.1 ppm and will be well far below the occupational Exposure Standard of 1.0 ppm on a time weighted average.

Formaldehyde may lead to temporary irritation to eyes, nose, and throat.

1



2



4. FIRST AID MEASURES

EYES

Flush eyes with large amounts of water. If irritation persists, get medical attention.

SKIN

Wash affected areas with soap and large amount of water. If persistent irritation or dermatitis occur get medical advice attention.

INHALATION

Remove to fresh air. Get medical advice if persistent irritation, severe coughing or breathing difficulty occurs.

INGESTION

Not applicable.

5. FIRE & EXPLOSION DATA

AUTO IGNITION TEMPERATURE

> 200C (will depend upon duration of exposure to heat source and other variables)

FLASH POINT

Not applicable.

EXTINGUISHING MEDIA

Water, Carbon dioxide, Sand

UNUSUAL FIRE AND EXPLOSION HAZARDS

Sawing, sanding or machining can produce wood dust which may present an explosion hazard if a dust cloud contacts an ignition source.

6. ACCIDENTAL RELEASE MEASURES

Not applicable.

3



Wood dust May cause nasal dryness, irritation and obstruction. Coughing, wheezing, and sneezing, sinusitis and prolonged colds have also been reported. Prolonged exposure to wood dust has been reported by some observers to be associated with nasal cancer. Wood dust is not listed as a carcinogen.

INGESTION

Not applicable as is not likely to occur.

3. COMPOSITION / INFORMATION ON INGREDIENTS

This panel product contains a 100% birch veneer face bonded to birch veneer using phenol-formaldehyde glue.

PANEL

100% pure birch (*Betula pendula*) veneer.

INGREDIENTS:

Component trade name	Exact chemical name* (IUPAC common name and CAS number)	Effect	Classification according to DIR 67/548/EEC or EC directive No. 1272/2008**	% of weight
Wood	n/a	Veneer Layers	-	~87-93
Phenol formaldehyde resin	CAS 9003-35-4	Production of waterproof plywood	500-005-2	~5-9
Natural chalk	Not listed, subject to sanitary assessment and Sanitary-epidemiological certificate should be issued	Serves to reduce water penetration into the wood pores, reduces glue shrinkage and increases glue bond strength. Chalk closes wood pores very well.	EU number - none, MACs of Harmful Substances in Occupational Air - not specified, Hazard class - none	~1-2
Flour	Not classified as a hazardous product according to international environmental regulations	Adds specific viscosity to the glue and eliminates internal stress in glue bond.	EU number - none, MACs of Harmful Substances in Occupational Air - not specified, Hazard class - none	~0.5-2

4. FIRST AID MEASURES

7. HANDLING AND STORAGE

Product is to be stored in a dry well ventilated space to reduce the formaldehyde concentration build up.

Product is combustible and should be kept away from ignition sources.

Care should be taken and necessary equipment shall be used when handling heavy loads of plywood.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

FORMALDEHYDE

Provide adequate ventilation to reduce the possible buildup of formaldehyde gas, particularly when high temperatures occur.

WOOD DUST

Machining equipment with exhaust devices/dust collecting equipment should be used to remove saw dust from the product. To be kept away from sources of radiant heat, flame sources, sparks and other possible sources of ignition.

PERSONAL PROTECTIVE EQUIPMENT

Goggles/safety glasses should be used product is being cut.

P1/P2 class respirator should be used against saw dust.

Loose comfortable clothing covering skin areas should be worn to minimize exposure to dust and splinters. Work gloves are necessary to minimize exposure and prevent splinters when handling panels.

9. PHYSICAL AND CHEMICAL DATA

APPEARANCE AND ODOR

Light to dark color. Color and odor are dependent upon wood.

BASIC PROPERTIES

State	Solid
Boiling point	Not applicable
Specific gravity (H2O=1)	<1
Vapor density	Not applicable
% volatiles by volume	0%
Melting point	Not applicable
Vapor pressure	Not applicable
Solubility in H2O (% by wt.)	<0.1%
Evaporation rate (butyl acetate = 1)	Not applicable
pH	Not applicable

4



10. STABILITY AND REACTIVITY DATA**CONDITIONS CONTRIBUTING TO INSTABILITY**

Stable under normal conditions.

INCOMPATIBILITY

Avoid contact with oxidizing agents. Combustible.

HAZARDOUS DECOMPOSITION PRODUCTS

Thermal and/or thermal oxidative decomposition can produce irritating and toxic fumes and gases, including carbon monoxide, hydrogen cyanide, aldehydes, organic acids and polynuclear aromatic compounds.

HAZARDOUS POLYMERIZATION

Not applicable.

11. TOXICOLOGICAL INFORMATION**FORMALDEHYDE**

Formaldehyde is listed on the International Agency for Research on Cancer (IARC) as a probable human carcinogen.

Formaldehyde is regulated by OSHA as a potential cancer agent. In studies involving rats, formaldehyde has been shown to cause nasal cancer after long-term exposure to very high concentration (14+ ppm). Far above those normally found in the workplace, using this product.

The National Cancer Institute (NCI) conducted an epidemiological study of industrial workers exposed to formaldehyde (published June 1986). The NCI concluded that the data provides little evidence that mortality from cancer is associated with formaldehyde exposure at the levels experienced by workers in the study.

WOOD DUST

Dust generated during machining of plywood is not classified as a potential cancer hazard by OSHA or the National Toxicology Program

IARC (International Agency of research for cancer) classifies wood dust as a carcinogen for humans due to potential risk in occurrence of adenocarcinomas of the nasal cavities and paranasal sinuses associated with exposure to wood dust.

12. ECOLOGICAL INFORMATION

Product is biodegradable.

No water hazard - Insoluble in water.

Product shall be utilized in efficient manner after end of lifecycle.

13. DISPOSAL CONSIDERATIONS

Refer to local regulations. Normally suitable for disposal at approved land waste site

14. TRANSPORT INFORMATION

UN Number: none allocated.

Dangerous goods class: none allocated.

Hazchem Code: none allocated.

15. REGULATORY INFORMATION

OSHA – not hazardous under the criteria OSHA 29CFR 1910.1200

TSCA – complies with TSCA inventory requirements

BARA 313 – none

Canadian WHMIS – not considered controlled

16. OTHER INFORMATION

Preparation date: March 28, 2018

DISCLAIMER: The information in this Material Safety Data Sheet (MSDS) is believed to be correct as of the date issued. SVEZA MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE.

User is responsible for determining whether the SVEZA product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a SVEZA product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluate the SVEZA product to determine whether it is fit for a particular purpose and suitable for user's method of use or application.

SVEZA provides information in electronic form as a service to its customers. Due to the remote possibility that electronic transfer may have resulted in errors, omissions or alterations in this information, SVEZA makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the MSDS available directly from SVEZA.